

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current. Please download the latest datasheet of PVM4A501C01B00 from the official website of Murata

# PVM4A501C01B00










### Appearance & Shape







#### **Features**

- 1. Sealed construction protects the interior from dust and liquid, which achieves stable performance.
- 2. Available for flow and reflow soldering methods while maintaining unique sealed construction.
- 3. Simple construction of 3-piece parts achieves high reliability.
- 4. Large diameter slot of rotor improves driver insertion.
- 5. Available for cleaning after soldering.



### Packaging Information

| Packaging | Specifications | Standard<br>Packing<br>Quantity |
|-----------|----------------|---------------------------------|
| B00       | Bulk(Bag)      | 500                             |

1 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





information provided may not be the most current.

Please download the latest datasheet of PVM4A501C01B00 from the official website of Murata

Note: If you have not downloaded this document from our official website, please note that the

# PVM4A501C01B00



# **Specifications**

| Power Rating                               | 0.1W                                      |  |
|--|---|--|
| Shape                                      | SMD                                       |  |
| Maximum Working Voltage                    | 50Vdc                                     |  |
| Adjustment Direction                       | Тор                                       |  |
| Size                                       | 4mm                                       |  |
| Auto Adjustment                            | Yes                                       |  |
| Number of Turns (Effective Rotation Angle) | 1(240°±10°)                               |  |
| Mechanical Rotation Angle                  | Endless                                   |  |
| Total Resistance Value                     | 500Ω                                      |  |
| Total Resistance Value<br>Tolerance        | ±25%                                      |  |
| Temperature Coefficient of Resistance      | ±250ppm/°C                                |  |
| Resistance Taper                           | B (Linear)                                |  |
| Contact Resistance Variation               | 3% max. of nominal total resistance value |  |
| Residual Resistance                        | 2% max. of nominal total resistance value |  |
| Soldering Method                           | Reflow,Soldering Iron                     |  |
| Torque                                     | 2.0 to 24.5mN · m                         |  |
| Measure Condition of RatedPower            | 70°C                                      |  |
| Operating Temperature<br>Range             | -55°C to 125°C                            |  |
| Mass                                       | 0.08g                                     |  |

2 of 3

#### Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no space for \ detailed \ specifications.}$ 

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






# PVM4A501C01B00

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of PVM4A501C01B00 from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=PVM4A501C01B00





Constructions

3 of 3

#### Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

