

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of PVG5H101C03R00 from the official website of Murata

PVG5H101C03R00










Appearance & Shape







Features

- 1. Sealed construction protects the interior from dust and liquid, which achieves stable performance.
- 2. Available with reflow soldering method
- 3. Available for ultrasonic cleaning after soldering
- 4. Clutch mechanism prevents excessive wiper rotation.
- 5. Both Top and side adjustment directions
- 6. Ultra smaller volume (1/5-1/2) than leaded multi-turn potentiometer.



Packaging Information

| Packaging | Specifications | Standard Packing Quantity |
|-----------|---------------------|---------------------------------|
| R00 | 180mm Embossed Tape | 500 |

1 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

 $Please\ download\ the\ latest\ data sheet\ of\ PVG5H101C03R00\ from\ the\ official\ website\ of\ Murata$

http://www.murata.com/en/products/productdetail?partno=PVG5H101C03R

PVG5H101C03R00



Specifications

| Power Rating | 0.25W | |
|--|--|--|
| Shape | SMD | |
| Maximum Working Voltage | 300Vdc | |
| Adjustment Direction | Side | |
| Size | 5mm | |
| Auto Adjustment | No | |
| Number of Turns (Effective Rotation Angle) | 11 | |
| Mechanical Rotation Angle | - | |
| Total Resistance Value | 100Ω | |
| Total Resistance Value Tolerance | ±10% | |
| Temperature Coefficient of Resistance | ±150ppm/°C | |
| Resistance Taper | B (Linear) | |
| Contact Resistance Variation | Less than 3% of total resistance value or 3ohm, whichever is greater | |
| Residual Resistance | Less than 1% of total resistance value or 20hm, whichever is greater | |
| Torque | 17.6mN ⋅ m max. | |
| Measure Condition of RatedPower | 70°C | |
| Operating Temperature Range | -55°C to 125°C | |
| Mass | 0.18g | |

2 of 3

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no space for \ detailed \ specifications.}$

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






PVG5H101C03R00

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of PVG5H101C03R00 from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=PVG5H101C03R00

Product Data



Constructions

3 of 3

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

