

Product Search Data Sheet

# CSTCC2M40G53-R0


Discontinued RoHS

REACH

### Applications

Unsuitable	Please be sure to read and comply with		
Applications	these "Precautions for use."		
Specific Applications	Consumer equipment		
	Please refer to Our Website and		
	specifications, etc. for information about		
	the performance, functions, quality,		
	management, and safety required for		
	the above applications, and use		
	Products after confirming the		
	performance and reliability of the actual		
	Product.		

### Appearance & Shape



(1): Input (2): GND (3): Output []: Frequency Marking (P1: Vender's Code 1: Vender's Code : EIAJ Monthly Code : 1.75±0.05 (2.00-2.99MHz) : 1.55±0.05 (3.00MHz-) Note: This datasheet may be out of date. Please download the latest datasheet of CSTCC2M40G53-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=CSTCC2M40G53-R0

## Packaging Information

	Packaging	Specifications	Standard Packing Quantity
	R0	180mm Embossed Tape	2000



MURATA's package technology expertise has enabled the development of the Chip CERALOCK. High-density mounting can be realized because of the small package and the elimination of the need for an external load capacitor.

#### Features

- 1. Oscillation circuits do not require external load capacitors.
- 2. Available in a wide frequency range.
- 3. Extremely small and have a low profile.
- 4. No adjustment is necessary for oscillation circuits.

1 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

- without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





# CSTCC2M40G53-R0

Note: This datasheet may be out of date. Please download the latest datasheet of CSTCC2M40G53-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=CSTCC2M40G53-R0

## Specifications

#### Ceramic Resonator Product Type (CERALOCK) Series CSTCC\_G Frequency 2.400MHz **Frequency Tolerance** +/-0.50% max. **Operating Temperature** -20°C~80°C Range Frequency Shift by +/-0.30% max. Temperature Frequency Aging +/-0.30% max. Resonant Impedance (R1) 80ohm max. Built-in Load Capacitance 15pF (CL1/CL2) Shape SMD Wash Not available L x W (size) 7.2x3.0mm Mass 92mg

2 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

