Product Search Data Sheet



# PVZ3K104E01B00

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.


Please download the latest datasheet of PVZ3K104E01B00 from the official website of Murata


http://www.murata.com/en-gb/products/productdetail?partno=PVZ3K104E01B00



Appearance & Shape







- 1. Excellent solderability characteristics are achieved via special plating techniques on each termination.
- 2. Specially designed substrate prevents wicking of flux onto the top of the part body.

### Packaging Information

Packaging	Specifications	Standard Packing Quantity
B00	Bulk(Bag)	1000

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# PVZ3K104E01B00

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of PVZ3K104E01B00 from the official website of Murata

http://www.murata.com/en-gb/products/productdetail?partno=PVZ3K104E01B00



#### Power Rating 0.1W SMD Shape 50Vdc Maximum Working Voltage Adjustment Direction Rear Size 3mm Yes Auto Adjustment Number of Turns (Effective 1(230°±10°) Rotation Angle) Mechanical Rotation Angle Endless **Total Resistance Value** 100kΩ Total Resistance Value ±30% Tolerance Temperature Coefficient of ±500ppm/°C Resistance **Resistance Taper** B (Linear) 5% max. of nominal total Contact Resistance Variation resistance value 2% max. of nominal total **Residual Resistance** resistance value Soldering Method Soldering Iron, Reflow 2.0 to 19.6mN · m Torque Measure Condition of 50°C RatedPower **Operating Temperature** -25°C to 85°C Range 0.04g Mass

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

Product Search Data Sheet




## PVZ3K104E01B00

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of PVZ3K104E01B00 from the official website of Murata

http://www.murata.com/en-gb/products/productdetail?partno=PVZ3K104E01B00





Constructions

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

