

# 7BB-15-6

Note: This datasheet may be out of date. Please download the latest datasheet of 7BB-15-6 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=7BB-15-6

discontinued RoHS


IS REACH

### Applications

Unsuitable	Please be sure to read and comply with		
Applications	these "Precautions for use."		
	Consumer equipment,Industrial		
	Equipment		
	Please refer to Our Website and		
	specifications, etc. for information about		
Specific	the performance, functions, quality,		
Applications	management, and safety required for		
	the above applications, and use		
	Products after confirming the		
	performance and reliability of the actual		
	Product.		

# Packaging Information

	Packaging	Specifications	Standard Packing Quantity
	-	Bulk	8000




#### 1. Clear sound

- 2. Ultra thin and lightweight
- 3. No contacts: therefore, no noise and highly reliable
- 4. Low power consumption for voltage type



### Appearance & Shape



1 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





## 7BB-15-6

Note: This datasheet may be out of date. Please download the latest datasheet of 7BB-15-6 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=7BB-15-6

### Specifications

Resonance Frequency	6.0kHz
Resonant Frequency Torelance	±1.0kHz
Resonant Impedance (R1)	800Ω
Capacitance	10nF
Capacitance Tolerance	±30%
Measurement Condition of Capacitance	[1kHz]
Operating Temperature Range	-20°C to 70°C
Storage Temperature Range	-30℃ to 80℃
Shape	No lead wire
Plate Size	15mm
Element Size	10mm
Plate Material	Brass
Drive Type	External Drive
EIAJ Part Number	PD-SU2-C15-60
Mass	241mg

2 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

