

LLA219R71E103MA01#

Note: This datasheet may be out of date.

Please download the latest datasheet of LLA219R71E103MA01# from the official website of Murata

http://www.murata.com/en-gb/products/productdetail?partno=LLA219R71E103MA01%2

"#"at the end indicates the package specification code.













< List of part numbers with package codes > LLA219R71E103MA01L



Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
Specific Applications	Consumer equipment,Industrial Equipment,Mobile Electronics,Medical equipment [GHTF A/B/C] except for implant equipment,Automotive infotainment/comfort equipment Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use Products after confirming the performance and reliability of the actual Product.



Manufacturing Co., Ltd.

References


Packaging	Specifications	Standard Packing Quantity
L	180Embossed Tape	3000

Mass (typ.)		
1 piece	11.0mg	



Appearance & Shape





1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





LLA219R71E103MA01#

Note: This datasheet may be out of date.

Please download the latest datasheet of LLA219R71E103MA01# from the official website of Murata $\,$ Manufacturing Co., Ltd.

"#"at the end indicates the package specification code.



Specifications

Length	2.0±0.1mm
Width	1.25±0.1mm
Thickness	0.85±0.1mm
Capacitance	10000pF ±20%
Distance between external terminals P	0.5±0.05mm
Operating Temperature Range	-55°C to 125°C
Rated Voltage	25Vdc
Size code in inch(mm)	0805 (2012M)
Capacitance change rate	±15.0%
Temperature characteristics (complied standard)	X7R(EIA)
Temperature range of temperature characteristics	-55°C to 125°C

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

