

Product Search Data Sheet

# CFUKF455KA2X-R0

Discontinued RoHS


HS REACH

## Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
Specific Applications	Consumer equipment
	Please refer to Our Website and
	specifications, etc. for information about
	the performance, functions, quality,
	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.



## Appearance & Shape




Note: This datasheet may be out of date. Please download the latest datasheet of CFUKF455KA2X-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=CFUKF455KA2X-R0

## Packaging Information

Packaging	Specifications	Standard Packing Quantity
-R0	180mm Embossed Tape	450



The CFUKF series is comprised of small, high-performance, thin (4.0mm) filters consisting of 4 ceramic elements. The filters exhibit an extremely flat GDT characteristic. The filters are recommended for digital communication applications and are perfect in handheld cellular phones, etc.

## Features

1. The filters are mountable by automatic placers.

2. The filters can be reflow soldered and withstand washing.

3. They are slim, at only 4.0mm maximum thickness, and have a small mounting area (7.5x6.0mm) enabling flexible PCB design. 4. The bandwidth ranges from Ato E.

5. Operating temperature range: -20 to +80 (degrees C), Storage temperature range: -40 to +85 (degrees C)

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





# CFUKF455KA2X-R0

Note: This datasheet may be out of date. Please download the latest datasheet of CFUKF455KA2X-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=CFUKF455KA2X-R0

## Specifications

#### **Operating Temperature** -20°C to 80°C Range SMD Shape 4 Elements **Center Frequency** 455.0kHz Center Frequency Tolerance ±2kHz Nominal Center Value No 6dB Bandwidth fn±17.5kHzmin. Stop Bandwidth 40.0kHz Area of Stop Bandwidth [within 40dB] Stop Band Attenuation 25dB[within fn±100kHz] Insertion Loss 4.0dB[at minimum loss point] Ripple 1.0dB[within fn±12kHz] **GDT** Deviation 15.0µs[within fn±12kHz] Input/Output Impedance 1000Ω 504mg Mass

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.










# CFUKF455KA2X-R0

Note: This datasheet may be out of date. Please download the latest datasheet of CFUKF455KA2X-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=CFUKF455KA2X-R0








**Frequency Characteristics** 

**Spurious Response** 



**Measurement Circuit** 

3 of 3

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

