

NOVATOR IN ELECTRONICS

Note: This datasheet may be out of date.

Please download the latest datasheet of IRA-S510ST01 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=IRA-S510ST01

IRA-S510ST01











Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Consumer equipment
	Please refer to Our Website and
	specifications, etc. for information about
Specific	the performance, functions, quality,
Applications	management, and safety required for
Applications	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.
Recommended	Intrusion detection,Security Equipment,
Applications	Light



Packaging Information

	Packaging	Specifications	Standard Packing Quantity
	-	Вох	100




Features

Excellent Sensitivity & S/N ratio (Signal/Noise) Excellent Quality



Appearance & Shape





1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





IRA-S510ST01

Note: This datasheet may be out of date.

Please download the latest datasheet of IRA-S510ST01 from the official website of Murata

http://www.murata.com/en-gb/products/productdetail?partno=IRA-S510ST01

Manufacturing Co., Ltd.



Specifications

Shape	Lead
Dimensions	TO-5(φ9.2x4.7mm)
Output Type	Analog
Electrode	(1.0x1.0mm)x4
Responsivity(typ.)	3.3mV
Supply Voltage Range	2V to 15V
Field of View	theta1=theta2=44deg.
Operating Temperature Range	-40°C to 70°C
Storage Temperature Range	-40°C to 85°C

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of IRA-S510ST01 from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-gb/products/productdetail?partno=IRA-S510ST01

IRA-S510ST01






(in mm)



Pyroelectric Elements(Electrode Dimension)



Optical Filter characteristics

Test system of Responsivity

3 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

