

LFL18628MTC2C221

In Production

Recommended

RoHS

REACH


Applications

| | |
|--------------------------|---|
| Unsuitable Applications | Please be sure to read and comply with these "Precautions for use." |
| Specific Applications | Consumer equipment,Industrial Equipment,Medical equipment [GHTF A/B],Mobile Electronics Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use Products after confirming the performance and reliability of the actual Product. |
| Recommended Applications | Consumer equipment,Industrial Equipment,Medical equipment [GHTF A/B],Mobile Electronics |

Packaging Information

| Packaging | Specifications | Standard Packing Quantity |
|-----------|------------------|---------------------------|
| - | 180mm Paper Tape | 4000 |

Appearance & Shape



Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

LFL18628MTC2C221



Features

small, low-profiled, lightweight chip filters based on ceramic multilayer technology.

Offering stable high selectivity up to very high frequency.

1. Low loss
2. Ultra-small, low-profiled, lightweight low-pass filters.
3. Ideal for removing high-frequency harmonics at power amplifier and IF stage.
4. Available in tape and reel packings for automatic mounting.
5. Absolutely no adjustment required.
6. Reflow solderable.
7. Center frequencies and responses are ready for customization. Samples are available in a short lead time.

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

LFL18628MTC2C221



Specifications

| | |
|----------------------------------|--------------------------------------|
| Applications | LTE Band13 |
| Nominal Center Frequency (fo) | 628.50MHz |
| Bandwidth(BW) | fo±158.50MHz |
| Insertion Loss in BW I) | 0.65dB max. (at 25°C) |
| Insertion Loss in BW II) | 0.71dB max. (-40 to +85°C) |
| Attenuation(Absolute Value) I) | 26.0dB min. at 1429.00 to 1501.00MHz |
| Attenuation(Absolute Value) II) | 30.0dB min. at 1565.00 to 1607.00MHz |
| Attenuation(Absolute Value) III) | 35.0dB min. at 1570.00 to 1580.00MHz |
| Attenuation(Absolute Value) IV) | 18.0dB min. at 1920.00 to 1980.00MHz |
| VSWR(max.) | 1.8 |
| Characteristic Impedance (Nom.) | 50Ω |
| Power Capacity | 3W |
| Operating Temperature Range | -40°C to 85°C |
| L x W (size) | 1.60x0.80mm |
| Thickness(max.) | 0.7mm |

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.