Product Search Data Sheet



PVZ3G224C01B00


Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of PVZ3G224C01B00 from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=PVZ3G224C01B00



Appearance & Shape





- 1. Excellent solderability characteristics are achieved via special plating techniques on each termination.
- 2. Specially designed substrate prevents wicking of flux onto the top of the part body.

Packaging Information

| Packaging | Specifications | Standard Packing Quantity |
|-----------|----------------|---------------------------------|
| B00 | Bulk(Bag) | 1000 |

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





PVZ3G224C01B00

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of PVZ3G224C01B00 from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=PVZ3G224C01B00

Specifications

| Power Rating | 0.1W | |
|---|---|--|
| Shape | SMD | |
| Maximum Working Voltage | 50Vdc | |
| Adjustment Direction | Тор | |
| Size | 3mm | |
| Auto Adjustment | Yes | |
| Number of Turns (Effective Rotation Angle) | 1(230°±10°) | |
| Mechanical Rotation Angle | Endless | |
| Total Resistance Value | 220kΩ | |
| Total Resistance Value Tolerance | ±30% | |
| Temperature Coefficient of Resistance | ±500ppm/°C | |
| Resistance Taper | B (Linear) | |
| Contact Resistance Variation | 5% max. of nominal total resistance value | |
| Residual Resistance | 2% max. of nominal total resistance value | |
| Torque | 1.0 to 19.6mN ⋅ m | |
| Measure Condition of RatedPower | 50°C | |
| Operating Temperature Range | -25℃ to 85℃ | |
| Mass | 0.02g | |

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Product Search Data Sheet




Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

 $\label{eq:please} Please \ download \ the \ latest \ data sheet \ of \ PVZ3G224C01B00 \ from \ the \ of \ ficial \ website \ of \ Murata$

http://www.murata.com/en/products/productdetail?partno=PVZ3G224C01B00

PVZ3G224C01B00





Constructions

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.