

Product Search Data Sheet

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of NCP03WB473E05RL from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=NCP03WB473E05R

NCP03WB473E05RL












Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Consumer equipment, Medical
	equipment [GHTF A/B]
	Please refer to Our Website and
	specifications, etc. for information about
Specific	the performance, functions, quality,
Applications	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.



Appearance & Shape







Packaging Information

Packaging	Specifications	Standard Packing Quantity
RL	180mm Paper Tape	15000



Features

- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-Constant
- 4. Reflow soldering possible
- 5. Lead is not contained in the product.
- 6. UL/cULcertified product.(UL1434, File No. E137188)

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current. Please download the latest datasheet of NCP03WB473E05RL from the official website of Murata

NCP03WB473E05RL



Specifications

	T T
Resistance (25°C)	47kΩ
Resistance Value Tolerance (at 25°C)	±3%
B-Constant (25/50°C)	4050K
B-Constant (25/50°C) Tolerance	±1%
B-Constant(25/80°C) (Reference Value)	4101K
B-Constant(25/85°C) (Reference Value)	4108K
B-Constant(25/100°C) (Reference Value)	4131K
Max. Voltage	5V
Maximum Operating Current (25°C)	0.046mA
Typical Dissipation Constant (25°C)	1mW/°C
Operating Temperature Range	-40°C to 125°C
Size Code (in mm)	0.6x0.3mm
Size Code (in inch)	0.2x0.1inch
Shape	SMD
Mass	0.00026g
MSL	1

- Glossary of NTC thermistors
- > Related documents (UL, RoHS, etc.)

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.


Please download the latest datasheet of NCP03WB473E05RL from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=NCP03WB473E05F


NCP03WB473E05RL



Product Data



Resistance-Temperature Characteristics



NCP03WB473*05RL 6.0 0.60 Max. Voltage Max. Operating Voltage Max. Operating Current 5.0 0.50 Operating Voltage (V) 0.40 € 05.0 C. Operating Curre 3.0 Max. Voltage / Max. 2.0 0.20 0.10 ___ 0.00 150 100 Temperature (°C)

Max. Voltage, Max. Operating Voltage/Current Reduction Curve

Temperature Error Characteristics

3 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

