

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of NTSD1XR502FPB30 from the official website of Murata

NTSD1XR502FPB30










Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Industrial Equipment
	Please refer to Our Website and
	specifications, etc. for information about
Specific	the performance, functions, quality,
Specific Applications	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.



Appearance & Shape





Type	L (mm)
NTSD1_FPB30	30
NTSD1_FPB40	40
NTSD1_FPB50	50



Packaging Information

Packaging		Standard Packing Quantity
-	Bulk(Bag)	500



Features

- 1. Electric insulation on lead wire
- 2. Excellent bending resistance due to suitable hardness of surface coating
- 3. Easy handling due to most suitable hardness of surface of coating
- 4. +/-1% of resistance and B-Constant tolerance is realized due to uniform thickness by the precise sheet forming method.

1 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of NTSD1XR502FPB30 from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=NTSD1XR502FPB

NTSD1XR502FPB30



Specifications

5kΩ
±1%
3700K
±1%
3727K
3738K
3760K
0.17mA
15.0mW
1.5mW/℃
-40°C to 125°C
7s
Insulation type
Lead
0.1g
N

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no space for \ detailed \ specifications.}$

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.


Please download the latest datasheet of NTSD1XR502FPB30 from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=NTSD1XR502FPB

NTSD1XR502FPB30



Product Data



Temperature Tolenrance-Temperature Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

