

Product Search Data Sheet

PKM30SPTH2501-B0

Discontinued RoHS REACH

Applications

Uns	suitable	Please be sure to read and comply with
App	olications	these "Precautions for use."
		Consumer equipment,Industrial
		Equipment
		Please refer to Our Website and
		specifications, etc. for information about
Spe	ecific	the performance, functions, quality,
App	Applications	management, and safety required for
		the above applications, and use
		Products after confirming the
		performance and reliability of the actual
		Product.

Note: This datasheet may be out of date. Please download the latest datasheet of PKM30SPTH2501-B0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=PKM30SPTH2501-B0

Packaging Information


Packaging	Specifications	Standard Packing Quantity
-B0	Bulk	70



Piezoelectric sounder self drive type requires only simple circuit and DC power supply. Since this type uses resonant system, it is also available for alarms which need large sound volume.

Appearance & Shape





1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





PKM30SPTH2501-B0

Note: This datasheet may be out of date. Please download the latest datasheet of PKM30SPTH2501-B0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=PKM30SPTH2501-B0

Specifications

Oscillation circuits	Not built-in
Size	30.5×7.7×33.25 mm
Frequency	2.5kHz
Sound Pressure Level	75dB (min.)
Measure Condition of Sound Pressure Level	[12Vdc,10cm]
Oscillating Frequency	2.5kHz
Measure Condition of Oscillation Frequency	[12Vdc]
Current Consumption(max.)	20mA
Measure Condition of Current Consumption	[12Vdc]
Maximum input voltage	3Vdc to 20Vdc
Operating Temperature Range	-20°C to 70°C
Storage Temperature Range	-30°C to 80°C
Shape	Lead
Lead Shape	Pin type
Lead length	Lead length:4.0mm
Drive Type	Self Drive
EIAJ Part Number	PS-RP3-V33-25
Mass	3599mg

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.









PKM30SPTH2501-B0

Note: This datasheet may be out of date. Please download the latest datasheet of PKM30SPTH2501-B0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=PKM30SPTH2501-B0

Product Data





Tr: 2SC1815Y or equivalent

Voltage Characteristics

Recommended Circuit

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



3 of 3