

Product Search Data Sheet

## PRF21BB471QB1RA

Discontinued RoHS

REACH


## Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Consumer equipment, Industrial
	Equipment
	Please refer to Our Website and
	specifications, etc. for information about
Specific	the performance, functions, quality,
Applications	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.

## Appearance & Shape



	g	e					
Part Number	Dimensions (mm)						
Part Nulliber	L	w	Т	е	g		
PRF03_RL	0.6±0.05	0.3±0.05	0.3±0.05	0.1 to 0.2	-		
	10+005	05+005	05+005	$0.1 \pm 0.04$	030		



Note: This datasheet may be out of date. Please download the latest datasheet of PRF21BB471QB1RA from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=PRF21BB471QB1RA

## Packaging Information

Packaging	Specifications	Standard Packing Quantity
RA	180mm Embossed Tape	4000



1. SMD type is helpful for miniaturizing circuits because of its small size and light weight.

- 2. Excellent thermal response due to small size
- 3. Solid-state construction provides excellent resistance to
- mechanical vibration and impact resistance.
- 4. Contactless operation provides noiseless operation.
- 5. ULcertified product. (UL1434, File No. E137188)

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# PRF21BB471QB1RA

Note: This datasheet may be out of date. Please download the latest datasheet of PRF21BB471QB1RA from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=PRF21BB471QB1RA

## Specifications

Max. Voltage	32V
Sensing Temperature	115℃
Sensing Temperature Tolerance	±5°C
Measure Condition of Sensing Temperature	at 4.7k ohm
Resistance (25°C)	470Ω
Resistance Value Tolerance (at 25°C)	±50%
Operating Temperature Range	-20°C to 130°C
Size Code (in mm)	2.0x1.25mm
Size Code (in inch)	0.8x0.5inch
Shape	SMD
Mass	0.011g
MSL	1

2 of 3

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Product Search Data Sheet




Note: This datasheet may be out of date. Please download the latest datasheet of PRF21BB471QB1RA from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=PRF21BB471QB1RA




INNOVATOR IN ELECTRONICS

## **Product Data**



**Resistance-Temperature Characteristics** 



Resistance-Temperature Characteristics Range (Reference)

3 of 3

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

