

Product Search Data Sheet

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of DLW21SH900HQ2# from the official website of Murata

http://www.murata.com/en-sg/products/productdetail?partno=DLW21SH900HQ2%23

"#"at the end indicates the package specification code.

In Production AEC- RoHS REACH

DLW21SH900HQ2#

< List of part numbers with package codes > DLW21SH900HQ2B DLW21SH900HQ2L




Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Automotive powertrain/safety equipment,
	Automotive infotainment/comfort
	equipment,Consumer equipment,
	Medical equipment [GHTF A/B/C]
	except for implant & surgery & auto
	injector,Industrial Equipment
Specific	Please refer to Our Website and
Applications	specifications, etc. for information about
	the performance, functions, quality,
	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.
Recommended	Automotive powertrain/safety equipment,
	USB2.0,LVDS,HDMI 1.4b,HDMI 2.0,
Applications	USB3.1 Gen2

Appearance & Shape







Packaging Information

Pack	kaging	Specifications	Standard Packing Quantity
В		Bulk(Bag)	500
L		180mm Embossed Tape	2000



1. Small size: 2.0x1.2x1.2mm

2. Available for high density mounting (Narrow pitch)

Application

Common mode noise suppression for automotive interfaces such as USB,LVDS,PCIe



Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





DLW21SH900HQ2#

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of DLW21SH900HQ2# from the official website of Murata

http://www.murata.com/en-sg/products/productdetail?partno=DLW21SH900HQ2%23

"#"at the end indicates the package specification code.



Specifications

Brand	Murata	

Shape	SMD
Size Code (in mm)	2012
Size Code (in inch)	0805
Length	2.0mm
Length Tolerance	±0.2mm
Width	1.2mm
Width Tolerance	±0.2mm
Thickness	1.2mm
Thickness Tolerance	±0.2mm
Common Mode Impedance (at 100MHz)	90Ω
Common Mode Impedance (at 100MHz) Tolerance	±25%
Rated Current	280mA
Derating of Rated Current	Yes (Over 105°C) *For details, please check the derating diagram.
Rated Voltage	20Vdc
Withstanding Voltage	50Vdc
DC Resistance(max.)	0.416Ω
DC Resistance	0.32Ω±30%
Insulation Resistance(min.)	10ΜΩ
Operating Temperature Range	-40°C to 125°C
Mass(typ.)	0.011g
Number of Circuit	1
Operating Temperature Range(Self-temperature rise is included)	No

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

Product Search Data Sheet



DLW21SH900HQ2#


Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.


Please download the latest datasheet of DLW21SH900HQ2# from the official website of Murata

w.murata.com/en-sg/products/productdetail?partno=DLW21SH900HQ2%23

"#"at the end indicates the package specification code.








Impedance-Frequency Characteristics


In operating temperature exceeding +105°C, derating of current is necessary for this series. Please apply the derating curve shown in chart according to the operating temperature.

Derating of Rated Current



Derating of Rated Current

Impedance-Frequency Characteristics (Main Items)



Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



without advance notice. Please check with our sales representatives or product engineers before ordering. 2. This datasheet has only typical specifications because there is no space for detailed specifications