

## 7BB-41-2C

http://www.murata.com/en-us/products/productdetail?partno=7BB-41-2C

Note: This datasheet may be out of date.










## **Applications**

Unsuitable	Please be sure to read and comply with		
Applications	these "Precautions for use."		
	Consumer equipment,Industrial		
	Equipment		
	Please refer to Our Website and		
	specifications, etc. for information about		
Specific	the performance, functions, quality,		
Applications	management, and safety required for		
	the above applications, and use		
	Products after confirming the		
	performance and reliability of the actual		
	Product.		



## Appearance & Shape







# Packaging Information

Please download the latest datasheet of 7BB-41-2C from the official website of Murata Manufacturing

Packaging	Specifications	Standard Packing Quantity
-	Bulk	400



## **Features**

- 1. Clear sound
- 2. Ultra thin and lightweight
- 3. No contacts: therefore, no noise and highly reliable
- 4. Low power consumption for voltage type

1 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# 7BB-41-2C

Note: This datasheet may be out of date.

Please download the latest datasheet of 7BB-41-2C from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=7BB-41-2C



# **Specifications**

Resonance Frequency	2.2kHz	
Resonant Frequency	±0.3kHz	
Torelance	10.3KHZ	
Resonant Impedance (R1)	250Ω	
Capacitance	24nF	
Capacitance Tolerance	±30%	
Measurement Condition of	[1kHz]	
Capacitance		
Operating Temperature	-20°C to 70°C	
Range	20 € 10 70 €	
Storage Temperature Range	-30°C to 80°C	
Shape	No lead wire	
Plate Size	41mm	
Element Size	25mm	
Plate Material	Brass	
Drive Type	Self Drive	
EIAJ Part Number	PD-SU3-C41-22	
Mass	5350mg	

2 of 2

### Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

