

Note: This datasheet may be out of date.

Please download the latest datasheet of BLL18AG331A2E1H01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=BLL18AG331A2E1H01%23

"#"at the end indicates the package specification code.









< List of part numbers with package codes > BLL18AG331A2E1H01B



Applications

| Unsuitable | Please be sure to read and comply with |
|--------------|--|
| Applications | these "Precautions for use." |
| | Automotive powertrain/safety equipment, |
| | Automotive infotainment/comfort |
| | equipment,Consumer equipment, |
| | Medical equipment [GHTF A/B/C] |
| | except for implant & surgery & auto |
| | injector,Industrial Equipment |
| Specific | Please refer to Our Website and |
| Applications | specifications, etc. for information about |
| | the performance, functions, quality, |
| | management, and safety required for |
| | the above applications, and use |
| | Products after confirming the |
| | performance and reliability of the actual |
| | Product. |
| Recommended | Automotivo nowortrain/cofoty aguinment |
| Applications | Automotive powertrain/safety equipment |
| | |



Packaging Information

| | Packaging | Specifications | Standard |
|--|-----------|----------------|----------|
| | | | Packing |
| | | | Quantity |
| | В | Bulk(Bag) | 500 |



Appearance & Shape





1 of 4

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: This datasheet may be out of date.

Please download the latest datasheet of BLL18AG331A2E1H01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=BLL18AG331A2E1H01%2

"#"at the end indicates the package specification code.



Features

1.BLL18A series is designed to function nearly as a resistor at noise frequencies, which greatly reduces the possibility of resonance and leaves signal wave forms undistorted.

BLL18A series is effective in circuits without stable ground lines because BLL18A series does not need a connection to ground.

- 2.BLL18A series is effective in noise suppression in a wide frequency range (30MHz to several hundred MHz).
- 3.Lead-free Halogen-free is available.
- 4.Flow soldering. Corresponds to the welding implementation. (Not supported Reflow soldering.)
- 5.The material can be changed to a Cu wire according to the welding material as required.

2 of 4

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date.

Please download the latest datasheet of BLL18AG331A2E1H01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=BLL18AG331A2E1H01%2

"#"at the end indicates the package specification code.



Specifications

| Shape | Lead |
|---------------------------------|----------------|
| Length | 4.5mm |
| Length Tolerance | max. |
| Width | 3.0mm |
| Width Tolerance | max. |
| Thickness | 4.0mm |
| Thickness Tolerance | max. |
| Operating Temperature Range | -40°C to 150°C |
| Mass(typ.) | 0.13g |
| Number of Circuit | 1 |
| Rated Current (at 85°C) | 200mA |
| Rated Current (at 125°C) | 200mA |
| Rated Current (at 150°C) | 200mA |
| DC Resistance(max.) | 0.6Ω |
| Impedance (at 100MHz) | 330Ω |
| Impedance (at 100MHz) Tolerance | ±40% |

3 of 4

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






Note: This datasheet may be out of date.

Please download the latest datasheet of BLL18AG331A2E1H01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=BLL18AG331A2E1H01%2

"#"at the end indicates the package specification code.







Impedance-Frequency Characteristics

Equivalent Circuit

4 of 4

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

