

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of LQH5BPB1R5NT0# from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=LQH5BPB1R5NT0%2

"#"at the end indicates the package specification code.

105°C Operation Available













< List of part numbers with package codes > LQH5BPB1R5NT0K LQH5BPB1R5NT0L




Applications

| Unsuitable | Please be sure to read and comply with | |
|--------------|--|--|
| Applications | these "Precautions for use." | |
| | Consumer equipment,Medical | |
| | equipment [GHTF A/B/C] except for | |
| | implant & surgery & auto injector, | |
| | Industrial equipment except for | |
| | transportation & facility & energy | |
| | equipment | |
| Specific | Please refer to Our Website and | |
| Applications | specifications, etc. for information about | |
| | the performance, functions, quality, | |
| | management, and safety required for | |
| | the above applications, and use | |
| | Products after confirming the | |
| | performance and reliability of the actual | |
| | Product. | |
| Recommended | Company of a service manager | |
| Applications | Consumer equipment | |



Appearance & Shape





Notices

When rated current is applied to the products, inductance will be within ±30% of nominal inductance value. When rated current is applied to the products, the temperature rise caused by self-generated heat shall be limited to 40°C max. Keep the temperature (ambient temperature plus self-generation of heat) under 125°C.

1 of 5

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.





Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of LQH5BPB1R5NT0# from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=LQH5BPB1R5NT0%2

"#"at the end indicates the package specification code.



References

| | | Standard |
|-----------|------------------|----------|
| Packaging | Specifications | Packing |
| | | Quantity |
| K | 330Embossed Tape | 3000 |
| L | 180Embossed Tape | 500 |

| Mass (typ.) | | |
|-------------|-------|-------|
| 1 | piece | 0.22g |

2 of 5

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.





Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of LQH5BPB1R5NT0# from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=LQH5BPB1R5NT0%2

"#"at the end indicates the package specification code.



Specifications

| L size | 5.0±0.2mm |
|--|--|
| W size | 5.0±0.2mm |
| T size | 2.0±0.2mm |
| Size code inch (mm) | 2020 (5050) |
| Inductance | 1.5µH±30% |
| Inductance Test Frequency | 100kHz |
| Rated current (Isat) (Based on Inductance change) | 5A(Max.) / 6.6A(Typ.) |
| Rated current (Itemp) (Based on Temperature rise) | Ambient temp.85°C 3A(Max.) 4.2A(Typ.)Ambient temp. 105°C 1.63A(Max.) |
| Max. of DC resistance | 0.0288Ω |
| DC resistance | 0.024Ω±20% |
| Operating Temperature Range (Self-temperature rise is included) | -40°C to 125°C |
| Operating Temperature Range(Self-temperature rise is not included) | -40°C to 105°C |
| Class of magnetic shield | Shielded (Magnetic Resin) |
| Self resonance frequency (min.) | 70MHz |
| Brand | Murata |
| Series | LQH5BPB_T0 |

3 of 5

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$



Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current. Please download the latest datasheet of LQH5BPB1R5NT0# from the official website of Murata


LQH5BPB1R5NT0#


"#"at the end indicates the package specification code.





Characteristic Data

The charts below may show another part number which shares its characteristics.









4 of 5

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.






Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of LQH5BPB1R5NT0# from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=LQH5BPB1R5NT0%2

"#"at the end indicates the package specification code.



LQH5BPB1R5NTO Temp. rise

5 of 5

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

