

Product Search Data Sheet

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current. Please download the latest datasheet of CSTCR4M09G53-R0 from the official website of Murata

CSTCR4M09G53-R0












Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
Specific Applications	Consumer equipment,Industrial equipment except for transportation & facility & energy equipment,Medical equipment [GHTF A/B],Mobile Electronics Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use Products after confirming the performance and reliability of the actual Product.	



Appearance & Shape





Packaging Information

Packaging	Specifications	Standard Packing Quantity
R0	180mm Embossed Tape	3000



Features

MURATA's package technology expertise has enabled the development of the Chip CERALOCK. High-density mounting can be realized because of the small package and the elimination of the need for an external load capacitor.

Features

- 1. Oscillation circuits do not require external load capacitors.
- 2. Available in a wide frequency range.
- 3. Extremely small and have a low profile.
- 4. No adjustment is necessary for oscillation circuits.

1 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of CSTCR4M09G53-R0 from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=CSTCR4M09G53-F

CSTCR4M09G53-R0



Specifications

Draduct Tura	Ceramic Resonator	
Product Type	(CERALOCK)	
Series	CSTCR_G	
Frequency	4.096MHz	
Frequency Tolerance	+/-0.50% max.	
Operating Temperature	20%5 20%5	
Range	-20°C~80°C	
Frequency Shift by		
Temperature	+/-0.20% max.	
	10.100	
Frequency Aging	+/-0.10% max.	
Resonant Impedance (R1)	60ohm max.	
Built-in Load Capacitance		
(CL1/CL2)	15pF 	
Shape	SMD	
Wash	Not available	
L x W (size)	4.5x2.0mm	
Mass	29mg	

2 of 2

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

