

Product Search Data Sheet

CSTCR6M29G53-R0


In Production Recommended RoHS REACH

Applications

| Unsuitable | Please be sure to read and comply with | |
|--------------------------|--|--|
| Applications | these "Precautions for use." | |
| Specific Applications | Consumer equipment,Industrial | |
| | equipment except for transportation & | |
| | facility & energy equipment,Medical | |
| | equipment [GHTF A/B],Mobile | |
| | Electronics | |
| | Please refer to Our Website and | |
| | specifications, etc. for information about | |
| | the performance, functions, quality, | |
| | management, and safety required for | |
| | the above applications, and use | |
| | Products after confirming the | |
| | performance and reliability of the actual | |
| | Product. | |

Appearance & Shape





Note: This datasheet may be out of date. Please download the latest datasheet of CSTCR6M29G53-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=CSTCR6M29G53-R0

Packaging Information

| | Packaging | Specifications | Standard Packing Quantity |
|--|-----------|---------------------|---------------------------------|
| | R0 | 180mm Embossed Tape | 3000 |



MURATA's package technology expertise has enabled the development of the Chip CERALOCK. High-density mounting can be realized because of the small package and the elimination of the need for an external load capacitor.

Features

- 1. Oscillation circuits do not require external load capacitors.
- 2. Available in a wide frequency range.
- 3. Extremely small and have a low profile.
- 4. No adjustment is necessary for oscillation circuits.



Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





CSTCR6M29G53-R0

Note: This datasheet may be out of date. Please download the latest datasheet of CSTCR6M29G53-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=CSTCR6M29G53-R0

Specifications

Ceramic Resonator Product Type (CERALOCK) Series CSTCR G Frequency 6.290MHz Frequency Tolerance +/-0.50% max. **Operating Temperature** -20°C~80°C Range Frequency Shift by +/-0.20% max. Temperature Frequency Aging +/-0.10% max. Resonant Impedance (R1) 50ohm max. Built-in Load Capacitance 15pF (CL1/CL2) Shape SMD Wash Not available L x W (size) 4.5x2.0mm Mass 29mg

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

