Product Search Data Sheet



TZC3R100AA01R00

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.


Please download the latest datasheet of TZC3R100AA01R00 from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=TZC3R100AA01R00



Appearance & Shape







1.Improve setting condition for adjusting tool by employing a big plus driver slot.

2.Improve corrosion resistance by Ni plating for Center axis.

3.Improve absorptive condition for vacuum nozzle of chip mounter.



Packaging Information

| Packaging | Specifications | Standard Packing Quantity |
|-----------|---------------------|---------------------------------|
| R00 | 180mm Embossed Tape | 1000 |

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





TZC3R100AA01R00

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of TZC3R100AA01R00 from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=TZC3R100AA01R00

Specifications

| Shape | SMD |
|--------------------------------|------------------------|
| Operating Temperature Range | -25℃ to 85℃ |
| Thickness | 1.6mm |
| Thickness Tolerance | ±0.1 |
| Rated Voltage | 100Vdc |
| Cmin.(max.) | ЗрF |
| Cmax. | 10pF |
| Cmax. Tolerance | +50/-0% |
| Adjustment Direction | Тор |
| тс | N750±300ppm/°C |
| Q | 500min. at 1MHz, Cmax. |
| Withstanding Voltage | 220Vdc |
| Insulation Resistance(min.) | 10000ΜΩ |
| Torque | 1.5 to 9.8mNm |
| Stator/Case Color | Black |
| Mass | 0.05g |

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Product Search Data Sheet




TZC3R100AA01R00

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of TZC3R100AA01R00 from the official website of Murata


http://www.murata.com/en-us/products/productdetail?partno=TZC3R100AA01R00

Product Data



Constructions





Temp. Coeff. Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

