

Product Search Data Sheet

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of RHS7G2A821J0K1H01B from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=RHS7G2A821J0K1H01B


RHS7G2A821J0K1H01B



Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	Automotive powertrain/safety equipment,	
	Automotive infotainment/comfort	
	equipment,Medical equipment [GHTF	
	A/B/C] except for implant equipment	
	Please refer to Our Website and	
Specific	specifications, etc. for information about	
Applications	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	

Appearance & Shape



Notices

HF(Halogen Free)、 Derating5



References

Packaging	Specifications	Standard Packing	
В	Bulk(Bag)	Quantity 500	
		1 1	

Mass (typ.)		
1 piece	0.1g	

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





RHS7G2A821J0K1H01B

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of RHS7G2A821J0K1H01B from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=RHS7G2A821J0K1H01B



Specifications

L size or Outer diameter D	3.9mm max.		
Width	3.5mm max.		
T size	2.6mm max.		
Lead spacing F	5.0±0.8mm		
Lead diameter d	0.5±0.05mm		
Paint dripping e	Up to the end of crimp		
Capacitance	820pF ±5%		
Rated voltage	100Vdc		
Temperature characteristics	CCG(MURATA)		
Temperature range of temperature characteristics	-55°C to 200°C		
Operating Temperature Range	-55°C to 200°C		
тс	-55°C to 25°C: 0+30/- 72ppm/°C 25°C to 125°C: 0±30ppm/°C 125°C to 200°C: 0+72/-30ppm/°C		
W1 size	6.0mm max.		

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

RHS7G2A821J0K1H01B


Please download the latest datasheet of RHS7G2A821J0K1H01B from the official website of Murata


http://www.murata.com/en-us/products/productdetail?partno=RHS7G2A821J0K1H01B



INNOVATOR IN ELECTRONIC

Characteristic Data





Capacitance - temperature characteristics

Impedance - frequency characteristics

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

3 of 3