

GRM21BB11E104KA01#

Note: This datasheet may be out of date.

Please download the latest datasheet of GRM21BB11E104KA01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GRM21BB11E104KA01%2

"#"at the end indicates the package specification code.













< List of part numbers with package codes > GRM21BB11E104KA01L GRM21BB11E104KA01K



Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	these "Precautions for use." Consumer equipment, Industrial Equipment, Mobile Electronics, Medical equipment [GHTF A/B/C] except for implant equipment, Automotive infotainment/comfort equipment Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use
	Products after confirming the performance and reliability of the actual
	Product.




Notices

Please use alternative.



Appearance & Shape







References

Packaging	Specifications	Standard Packing Quantity
L	180Embossed Tape	3000
К	330Embossed Tape	10000

Mass (typ.)		
1 piece	17.0mg	

1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





GRM21BB11E104KA01#

Note: This datasheet may be out of date.

Please download the latest datasheet of GRM21BB11E104KA01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GRM21BB11E104KA01%2

"#"at the end indicates the package specification code.



Specifications

1	0.0.0.4	
Length	2.0±0.1mm	
Width	1.25±0.1mm	
Thickness	1.25±0.1mm	
Capacitance	0.10µF ±10%	
Distance between external terminals g	0.7mm min.	
External terminal size e	0.2 to 0.7mm	
Operating Temperature Range	-25°C to 85°C	
Rated Voltage	25Vdc	
Size code in inch(mm)	0805 (2012M)	
Capacitance change rate	±10.0%	
Temperature characteristics	B(JIS)	
(complied standard)		
Temperature range of	-25°C to 85°C	
temperature characteristics		

2 of 2

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

