

Product Search Data Sheet

Note: This datasheet may be out of date.

Please download the latest datasheet of NCP21WF104J03RA from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NCP21WF104J03RA

NCP21WF104J03RA










Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Consumer equipment
	Please refer to Our Website and
	specifications, etc. for information about
Specific	the performance, functions, quality,
Specific	management, and safety required for
Applications	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.



Appearance & Shape







Packaging Information

Packaging	Specifications	Standard Packing Quantity
RA	180mm Embossed Tape	4000



Features

- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-constant
- 4. Flow / Reflow soldering possible
- 5. Same B-Constant in the same resistance in the three sizes (0805 size / 0603 size / 0402 size)

Easy to use smaller size in the circuits

- 6. Lead is not contained in the product.
- 7. UL/cULcertified product. (UL1434, File No. E137188)

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

(in mm)

 $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of NCP21WF104J03RA from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NCP21WF104J03RA

NCP21WF104J03RA



Specifications

Resistance (25°C)	100kΩ	
, ,	100/02	
Resistance Value Tolerance	±5%	
(at 25°C)		
B-Constant (25/50°C)	4250K	
B-Constant (25/50°C)	±3%	
Tolerance	157/0	
B-Constant(25/80°C)	4303K	
(Reference Value)	400010	
B-Constant(25/85°C)	4311K	
(Reference Value)	43111	
B-Constant(25/100°C)	4334K	
(Reference Value)	455410	
Max. Voltage	5V	
Maximum Operating Current	0.045 4	
(25°C)	0.045mA	
Typical Dissipation Constant	2mW/°C	
(25°C)	ZIIIVV/ C	
Operating Temperature	-40°C to 125°C	
Range	-40 C to 123 C	
Size Code (in mm)	2.0x1.25mm	
Size Code (in inch)	0.8x0.5inch	
Shape	SMD	
Mass	0.0094g	
MSL	1	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Product Search Data Sheet


Note: This datasheet may be out of date. Please download the latest datasheet of NCP21WF104J03RA from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-us/products/productdetail?partno=NCP21WF104J03RA

NCP21WF104J03RA



Product Data





Resistance-Temperature Characteristics

Maximum Operating Voltage Reduction Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

