

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of TZY2Z2R5AC01R00 from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=TZY2Z2R5AC01R00

TZY2Z2R5AC01R00











Appearance & Shape







Features

- 1. Small and thin size with external dimensions of 2.5(W)x3.2(L)x1.25max.(H)mm.
- 2. New shape of cover can improve the flux invasion compared with current products.
- 3. Improvement of the adhesion between rotor and stator leads to superior stability.
- 4. Unique construction with no plastic material provides superior soldering

heat resistance to maintain excellent characteristic performance after reflow soldering.



Packaging Information

Packaging	Specifications	Standard Packing Quantity
R00	180mm Embossed Tape	2000

1 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Floudel Sealell Data Silee

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of TZY2Z2R5AC01R00 from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=TZY2Z2R5AC01R0

TZY2Z2R5AC01R00



Specifications

Shape	SMD
Operating Temperature Range	-25°C to 85°C
Thickness	1.25mm
Thickness Tolerance	max.
Rated Voltage	25Vdc
Cmin.(max.)	1pF
Cmax.	2.5pF
Cmax. Tolerance	+100/-0%
Adjustment Direction	Тор
тс	NP0±300ppm/°C
Q	200min. at 200MHz, Cmax.
Withstanding Voltage	55Vdc
Insulation Resistance(min.)	10000ΜΩ
Torque	0.7 to 4.9mNm
Mass	0.032g

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.


Please download the latest datasheet of TZY2Z2R5AC01R00 from the official website of Murata

TZY2Z2R5AC01R00




Product Data





Constructions





Temp. Coeff. Characteristics

3 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

