


Product Search Data Sheet

PVM4A201D01B00

Discontinued RoHS REACH

Appearance & Shape





Note: This datasheet may be out of date. Please download the latest datasheet of PVM4A201D01B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=PVM4A201D01B00



- 1. Sealed construction protects the interior from dust and liquid, which achieves stable performance.
- 2. Available for flow and reflow soldering methods while maintaining unique sealed construction.
- 3. Simple construction of 3-piece parts achieves high reliability.
- 4. Large diameter slot of rotor improves driver insertion.
- 5. Available for cleaning after soldering.

Packaging Information

Packaging	Specifications	Standard Packing Quantity
B00	Bulk(Bag)	500

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





PVM4A201D01B00

Note: This datasheet may be out of date. Please download the latest datasheet of PVM4A201D01B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=PVM4A201D01B00

Specifications

Power Rating 0.25W SMD Shape 200Vdc Maximum Working Voltage Adjustment Direction Тор Size 4mm Yes Auto Adjustment Number of Turns (Effective 1(240°±10°) Rotation Angle) Mechanical Rotation Angle Endless **Total Resistance Value** 200Ω Total Resistance Value ±20% Tolerance Temperature Coefficient of ±100ppm/°C Resistance **Resistance Taper** B (Linear) 3% max. of nominal total Contact Resistance Variation resistance value 1% max. of nominal total **Residual Resistance** resistance value Soldering Method Reflow,Soldering Iron Torque 1.0 to 14.7mN · m Measure Condition of 70°C RatedPower **Operating Temperature** -55°C to 125°C Range Mass 0.08g

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Product Search Data Sheet




Note: This datasheet may be out of date. Please download the latest datasheet of PVM4A201D01B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=PVM4A201D01B00

PVM4A201D01B00





Constructions

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

