

GCM3195C2A103JA16J

Note: This datasheet may be out of date.

Please download the latest datasheet of GCM3195C2A103JA16# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=GCM3195C2A103.IA16%2

"#"at the end indicates the package specification code.















< List of part numbers with package codes > GCM3195C2A103JA16D GCM3195C2A103JA16J



Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Automotive powertrain/safety equipment,
	Automotive infotainment/comfort
	equipment,Medical equipment [GHTF
	A/B/C] except for implant equipment
	Please refer to Our Website and
Specific	specifications, etc. for information about
Applications	the performance, functions, quality,
	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.



References


	Specifications	Standard
Packaging		Packing
		Quantity
D	φ180mm Reel Paper Tape	4000
J	φ330mm Reel Paper Tape	10000

Mass (typ.)	
1 piece	19.0mg



Appearance & Shape





1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





GCM3195C2A103JA16J

Note: This datasheet may be out of date.

Please download the latest datasheet of GCM3195C2A103JA16# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=GCM3195C2A103.IA16%23

"#"at the end indicates the package specification code.



Specifications

Length	3.2±0.15mm	
Width	1.6±0.15mm	
Thickness	0.85±0.1mm	
Capacitance	10000pF ±5%	
Distance between external terminals g	1.5mm min.	
External terminal size e	0.3 to 0.8mm	
Operating Temperature Range	-55°C to 125°C	
Rated Voltage	100Vdc	
Size code in inch(mm)	1206 (3216M)	
TC	0±30ppm/°C	
Temperature characteristics	C0G(EIA)	
(complied standard)		
Temperature range of	25°C to 125°C	
temperature characteristics	20 C to 120 C	

2 of 2

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

