

Product Search Data Sheet

CFULA455KF4A-B0


Discontinued RoHS

HS REACH

Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
Specific Applications	Consumer equipment	
	Please refer to Our Website and	
	specifications, etc. for information about	
	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	

Appearance & Shape




Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of CFULA455KF4A-B0 from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=CFULA455KF4A-B0

Packaging Information

Packaging	Specifications	Standard Packing Quantity
-B0	Bulk	200



CFULAseries are high selectivity ceramic filters, which consist of 4 ceramic elements connected in a ladder form. They are most suitable for digital communications and cellular phones because of their improved GDT characteristics.

Features

- 1. High selectivity
- 2. Avariety of bandwidths available

3. Excellent GDT characteristics are available within pass bandwidth.

- 4. Easily mounted on a printed circuit board
- 5. Operating temperature range: -20 to +80 (degrees C), Storage temperature range: -40 to +85 (degrees C)

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





CFULA455KF4A-B0

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of CFULA455KF4A-B0 from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=CFULA455KF4A-B0



Operating Temperature -20°C to 80°C Range Shape Lead 4 Elements **Center Frequency** 455.0kHz Center Frequency Tolerance ±1.5kHz Nominal Center Value No 6dB Bandwidth fn±6.0kHzmin. Stop Bandwidth 12.5kHz Area of Stop Bandwidth [within 40dB] Stop Band Attenuation 27dB[within fn±100kHz] Insertion Loss 6.0dB[at minimum loss point] Ripple 1.5dB[within fn±4kHz] 2000Ω Input/Output Impedance Mass 1018mg

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Product Search Data Sheet




CFULA455KF4A-B0


Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of CFULA455KF4A-B0 from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=CFULA455KF4A-B0








Frequency Characteristics

Spurious Response



Measurement Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

